

## The Modern Stopcock Protecting property from the risk of water damage



## Welcome to surestop®

Surestop is a unique and innovative stopcock range, focused around protecting properties from the risk of water damage. With a simple flick of a switch, Surestop stopcocks will completely STOP the water supply - without the use of batteries or electrics. Surestop is easy and quick to install and use over traditional stopcocks.

### Why install a Surestop Stopcock instead of a brass stopcock?

- Instant protection - stops water with an easy flick of a switch
- No electrics or batteries involved, it works purely on the water pressure
- Provides ability to increase your annual sales
- Simply and quickly fitted in less than one hour
- Easy to use, easy to access and, unlike a brass stopcock it won't seize up
- WRAS approved as a stopcock
- Available with either push-fit fittings for simpler installation of pipe, or traditional compression
- Ideal for all residential and light commercial installations



Simply replace an existing brass stopcock or fit new



Turns off water instantly - no dripping taps



Powered by water, no need for electricity



Maintenance free - will never seize up



Works with cold and hot water

Proven performance throughout the UK, with over 1 million Surestop Stopcocks fitted.

### ✓ SURESTOP STOPCOCKS VS ✗ BRASS STOPCOCKS

Instantly stops water through a flick of a switch  
Easy to find and access; ideal for residents of varying ages and abilities  
Limescale resistant - won't seize up or corrode  
Lowers the risk of damage caused by a water leak

Susceptible to seizing up; making it longer and harder to stop the water  
Can be difficult and time consuming to locate and access  
Can corrode over time from limescale  
Increased risk of a water leak causing greater damage

# Surestop Stopcock with Remote Switch

## Benefits

- Instant and remote switch, for even simpler accessibility
- Can easily replace existing brass stopcocks
- WRAS approved as a stopcock (no 1011009)
- 15mm and 22mm options for installation with plastic or copper pipe
- Cold water supply max 23°C at 10 bar
- Limescale resistant
- Includes tubing options, to locate the remote switch up to 2m or 6m away\*
- Available with either push-fit fittings for simpler installation of pipe, or traditional compression
- Two year warranty



Product Code	Remote Switch Including Tubing		Push Fit	Compression Fitting	Plastic or Copper Pipe Sizes		Max Bar at 23°C	Gravity Fed Systems BAR Pressure to Open Valve
	2m	6m			15mm	22mm		
SS/15/RPL	●		●		●		10	0.5
SS/15/RCL	●			●	●		10	0.5
SS/22/RPL	●		●			●	10	0.5
SS/22/RCL	●			●		●	10	0.5
SS/15/RPL-06		●	●		●		10	0.5
SS/15/RCL-06		●		●	●		10	0.5
SS/22/RPL-06		●	●			●	10	0.5
SS/22/RCL-06		●		●		●	10	0.5

Minimum bar at all water temperatures is 0. \*We recommend no more than 6m of tubing.

## Surestop Stopcock

### Benefits

- Instant lockdown switch from the stopcock valve
- Can easily replace existing brass stopcocks
- WRAS approved as a stopcock (no 1011009)
- 15mm and 22mm options for installation with plastic or copper pipe
- Cold water supply max 23°C at 10 bar
- Limescale resistant
- Available with either push-fit fittings for simpler installation of pipe, or traditional compression
- Two year warranty



Product Code	Push Fit	Compression Fitting	Plastic or Copper Pipe Sizes		Max Bar at 23°C	Gravity Fed Systems BAR Pressure to Open Valve
			15mm	22mm		
SS/15/SPL	●		●		10	0.5
SS/15/SCL		●	●		10	0.5
SS/22/SPL	●			●	10	0.5
SS/22/SCL		●		●	10	0.5

Minimum bar at all water temperatures is 0.

## Surestop Stopcock MDPE

### Benefits

- Instant lockdown switch from the MDPE stopcock valve
- Can easily replace existing brass stopcocks
- Connects directly to the external blue MDPE pipe and internal pipe system
- WRAS approved as a stopcock (no 1011009)
- Cold water supply max 23°C at 10 bar
- 25mm MDPE push-fit inlet
- 15mm and 22mm push-fit outlet options
- Push-fit connection allows for easier installation of pipe
- Limescale resistant
- Two year warranty



Product Code	MDPE Inlet Push Fit	Plastic or Copper Push Fit Outlet		Max Bar at 23°C
	25mm	15mm	22mm	
SS/2515/NBP	●	●		10
SS/2522/NBP	●		●	10

Minimum bar at all water temperatures is 0.

### Remote Switch

Upgrade your standalone or MDPE stopcock to include a discreet remote switch.

**Product Code** SS/2M/UPK | **Description** Remote Switch and 2m Tubing Kit

**Product Code** SS/6M/UPK | **Description** Remote Switch and 6m Tubing Kit