

Polystorm Access provides a 1m x 0.5m shaft within a Polystorm geocellular structure to enable surface access for remote camera inspection and maintenance activities, such as flushing and rodding.

The system consists of a 500mm diameter shaft which extends from surface level to the top of a Polystorm structure, at which point a turret provides an interface between the shaft and the inspection chamber within the Polystorm structure. At the bottom of the chamber, a base unit interlocks with the surrounding layer of Polystorm cells whilst supporting the geomembrane. A 350mm reduced access shaft cap is provided to comply with inspection chamber regulations.


Polystorm Access is suitable for use with Polystorm, Polystorm-R, Polystorm Lite and Polystorm Xtra and may be combined with Polystorm Inspect for full length remote inspection and maintenance.



Please note: The Polystorm Access turret and base assembly are black. They are shown blue for illustration purposes.


## Key Benefits

- Meets minimum 450mm width requirement for inspection chamber access, with 350mm reduced access where regulations dictate
- Integrated solution; can be used with Polystorm Inspect to monitor internal volume of geocellular structure
- Base unit provides smooth transition between Polystorm Inspect units
- Multiple inspection configurations can be achieved when used in conjunction with Polystorm Inspect
- Manufactured from polyethylene for light weight, ease of handling and high strength
- Sustainability: All components 100% recyclable after use




**KEY**  
 Customer specified component parts of Polystorm Access  
 Included component parts of Polystorm Access

\* PSMA-B2 includes:  
 Polystorm Access Base Unit Qty: 2  
 Base Jointer Qty: 2  
 Base Connector Qty: 2  
 Seal Qty: 2



## Typical Elevation



Please note: Above is a typical installation detail for a Polystorm tank with groundwater below the base of the unit. For installation with groundwater above the structure invert please contact our Technical Team on **+44 (0) 1509 615100** or email [civils@polypipe.com](mailto:civils@polypipe.com)

## Polypipe Plastics Expertise

Polystorm Access is manufactured from sustainable polyethylene using the proven rotational moulding technique.

## Reliability and Performance

All components in the Polystorm Access system have a design life of up to 50 years where ground conditions allow.

## Easy Handling and Installation

Components are light and easy to handle, reducing health and safety risks and speeding up installation. The Polystorm Access shaft can be quickly and accurately cut to the right depth from 500mm Ridgidrain pipe, adding to the ease and flexibility on-site.

## Nominal Weights

PSMA-B2 = 8kg PSMA-T = 19kg PSMA-R = 4kg

## Flexible Positioning

The Polystorm Access turret can be positioned anywhere on a Polystorm structure, providing there are two or more Polystorm cells between the access turret and the structure edge.

The Polystorm Access shaft is variable in length depending on the depth you require.

## Features

- 1m x 0.5m inspection chamber within Polystorm structure
- 500mm riser shaft from surface to top of Polystorm structure
- Riser shaft may be extended as required using 500mm Ridgidrain pipe and seals
- It is recommended that the 500mm Ridgidrain pipe access shaft is within the limits of 250-1050mm for a standard installation
- Reduced Access shaft cap (350mm) available where required by regulations
- Utilises existing Polystorm Clips and Shear Connections
- Base unit manufactured from recyclable polyethylene
- Choice of standard shaft lengths

## Technical Support

Detailed guidance and assistance is available.

For further information, please contact our Technical Team on **+44 (0) 1509 615100** or email [civils@polypipe.com](mailto:civils@polypipe.com)

All descriptions and illustrations in this publication are intended for guidance only and shall not constitute a 'sale by description'. All dimensions given are nominal and Polypipe may modify and change the information, products and specifications from time to time for a variety of reasons, without prior notice. The information in this publication is provided 'as is' on January 2016. Updates will not be issued automatically. This information is not intended to have any legal effect, whether by way of advice, representation or warranty (express or implied). We accept no liability whatsoever (to the extent permitted by law) if you place any reliance on this publication you must do so at your own risk. All rights reserved. Copyright in this publication belongs to Polypipe and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person without prior consent. **Polypipe** is a registered trademark of Polypipe. All Polypipe products are protected by Design Right under CDPA 1988. Copyright © 2016 Polypipe. All rights reserved.