

DECLARATION OF PERFORMANCE No: Buildingservices/0713/005

Unique identification of the product-type	Air Admittance Valves Product Code: 253W (32mm, 40mm, 50mm) Product Code: 153.3.4 (82mm, 110mm)
Identification of the product	Product Code EAN Code Shop Order Number Date and time of manufacture
Intended use	To provide a method to protect water traps in gravity drainage systems when a negative pressure develops in the pipework
Contact	Polypipe Building Services College Road New Hythe Business Park Aylesford Kent ME20 7PJ
ACVP System	System 4

Declared Performances

Essential characteristics	Performance	hEN
Air Tightness	A (30Pa, 50Pa, 10,000Pa)	BS EN 12380:2002 Kitemark licence number KM554663
Durability (to withstand mechanical endurance, heat and temperatures below zero)	I (-20°C / +60°C)	
Effectiveness (airflow capacity)	32mm 6.6l/s 40mm 8.1l/s 50mm 9.5l/s 82mm 40.1l/s 110mm 43.2l/s	
Effectiveness (opening pressure)	0-150Pa	
Effectiveness at temperatures below zero	Pass	

The performance of the product identified above is in conformity with the declared performance.

Signed for and on behalf of Polypipe Building Services

25/02/2019
Polypipe
Aylesford Kent
Date and place of issue

Ian Crickmore
Technical Director
Name and function



Signature