

Our Gas Ducting is a PVCu single wall perforated duct supplied in yellow and manufactured to BS 4962. The perforations allow for gas to vent safely in the event of a leak.



Applications

For gas applications where utility companies stipulate the requirement for a perforated duct for the insertion of a gas pipe.

Key benefits

- Low weight, flexible, durable and high strength
- Kitemarked to BS 4962
- Available from stock
- Supplied with an integral coupler

GAS DUCTING

OD (mm)	LENGTH (m)	DESCRIPTION	CODE	COUPLING CODE
60	25	Perforated	LD6025YGAS	DC60
60	50	Perforated	LD6050YGAS	DC60
60	150	Perforated	LD60150YGAS	DC60
100	25	Perforated	LD10025YGAS	DC100M*
100	50	Perforated	LD10050YGAS	DC100M*

* Made from Polypropylene, other couplers are made from PVCu.

All descriptions and illustrations in this publication are intended for guidance only and shall not constitute a 'sale by description'. All dimensions given are nominal and Polypipe may modify and change the information, products and specifications from time to time for a variety of reasons, without prior notice. The information in this publication is provided 'as is' on February 2017. Updates will not be issued automatically. This information is not intended to have any legal effect, whether by way of advice, representation or warranty (express or implied). We accept no liability whatsoever (to the extent permitted by law) if you place any reliance on this publication you must do so at your own risk. All rights reserved. Copyright in this publication belongs to Polypipe and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person without prior consent. © Polypipe is a registered trademark of Polypipe. All Polypipe products are protected by Design Right under CDPA 1988. Copyright © 2017 Polypipe. All rights reserved.