

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name POLYPIPE GAP FILLER CEMENT GFC100
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives and/or sealants.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Polypipe Building Products
Broomhouse Lane
Edlington
Doncaster
DN12 1ES

Tel: 01709 770000

E-mail address bp.datasheets@polypipe.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650 (Bostik)
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 1 - (H318)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Flammable liquids	Category 2 - (H225)

2.2. Label elements

Contains Methyl ethyl ketone, Cyclohexanone



Signal word

Danger

Hazard statements

H318 - Causes serious eye damage.
H336 - May cause drowsiness or dizziness.
H225 - Highly flammable liquid and vapour.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking
EUH205 - Contains epoxy constituents. May produce an allergic reaction
EUH208 - Contains Bisphenol-A-Epichlorhydrin Epoxy resin (number average molecular weight ≤ 700). May produce an allergic reaction

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe fumes
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves and eye / face protection
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

Causes mild skin irritation. In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC)No. 1272/2008 [CLP]	Specific concentration limit(SCL)	REACH registration number
Methyl ethyl ketone	201-159-0	78-93-3	40 - <80	Eye Irrit. 2 (H319) (EUH066) STOT SE 3(H336) Flam. Liq. 2(H225)		01-2119457290-43-XXXX
Cyclohexanone	203-631-1	108-94-1	5 - <10	Acute Tox. 4(H332) Flam. Liq. 3(H226) Acute Tox. 4(H302) Acute Tox. 4(H312) Skin Irrit. 2(H315) Eye Dam. 1(H318)		01-2119453616-35-XXXX
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700	500-033-5	25068-38-6	0.1 - <1	Skin Irrit. 2(H315)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	01-2119456619-26-xxxx
MW				Eye Irrit. 2(H319) Skin Sens. 1(H317) Aquatic Chronic2 (H411)		

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Get immediate medical advice / attention. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon oxides. Hydrogen chloride. Silicon dioxide.

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk-through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk-through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

6.1. Reference to other sections

Reference to other sections	See section 8 for more information. See section 13 for more information.
------------------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.
General hygiene considerations	Do not eat, drink or smoke when using this product.

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

Recommended storage temperature

Keep at temperatures between 5 and 25 °C.

7.3. Specific end use(s)

Specific use(s)

Adhesives and/or sealants.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*
Cyclohexanone 108-94-1	TWA: 10 ppm TWA: 40.8 mg/m ³ STEL: 20 ppm STEL: 81.6 mg/m ³ *	TWA: 10 ppm TWA: 41 mg/m ³ STEL: 20 ppm STEL: 82 mg/m ³ Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl ethyl ketone 78-93-3	-	70 µmol/L (urine - Butan-2-one post shift)	70 µmol/L urine
Cyclohexanone 108-94-1	-	8 mg/L (urine - Cyclohexanol end of shift) 80 mg/L (urine - 1,2-Cyclohexanediol end of shift)	2 mmol/mol creatinine urine

Derived No Effect Level (DNEL)

Derived No Effect Level (DNEL)			
Methyl ethyl ketone (78-93-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	1161 mg/kg bw/d	

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

worker Long term Systemic health effects	Inhalation	600 mg/m ³	
--	------------	-----------------------	--

Cyclohexanone (108-94-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	100 mg/m ³	
worker Short term Systemic health effects	Inhalation	80 mg/m ³	
worker Long term Local health effects	Inhalation	40 mg/m ³	
worker Short term Local health effects	Inhalation	80 mg/m ³	
worker Long term Systemic health effects	Dermal	4 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	4 mg/kg bw/d	

Bisphenol-A-Epichlorohydrin Epoxy resin <= 700 MW (25068-38-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d	

Derived No Effect Level (DNEL)

Methyl ethyl ketone (78-93-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	106 mg/m ³	
Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d	

Cyclohexanone (108-94-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	20 mg/m ³	

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

Consumer Long term Systemic health effects	Dermal	20 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	5 mg/kg bw/d	

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Methyl ethyl ketone (78-93-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

Cyclohexanone (108-94-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0329 mg/l
Marine water	0.00329 mg/l
Freshwater sediment	0.168 mg/kg
Marine sediment	0.0168 mg/kg
Soil	0.0143 mg/kg

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.0006 mg/l
Freshwater sediment	0.996 mg/l
Marine sediment	0.0996 mg/l
Soil	0.196 mg/l

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection

Tight sealing safety goggles. Face protection shield.

Hand protection

Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves.

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection Antistatic footwear. Wear fire/flamm resistant/retardant clothing. Suitable protective clothing.

Respiratory protection In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Thixotropic
Colour	No information available
Odour	Characteristic
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	79 °C	
Flash point	-9 °C	
Evaporation rate	No data available	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

Vapour pressure	No data available
Relative vapour density	No data available
Relative density	No data available
Water solubility	No data available
Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available

9.2. Other information

Solid content (%)	No information available	
VOC Content (%)	790 g/L	European directive n°2010/75/UE
Density	0.90 g/cm ³	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	None.
----------------------------------	-------

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid	Heat, flames and sparks.
---------------------	--------------------------

10.5. Incompatible materials

Incompatible materials	Strong acids. Strong bases. Strong oxidising agents.
------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.
----------------------------------	--

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Redness. Burning. May cause blindness. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.
----------	--

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	19,336.60 mg/kg
ATEmix (dermal)	13,856.90 mg/kg
ATEmix (inhalation-dust/mist)	18.90 mg/l
ATEmix (inhalation-vapour)	138.60 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone 78-93-3	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Cyclohexanone 108-94-1	=1535 mg/kg (Rattus)	= 947 mg/kg (Oryctolagus cuniculus)	=8000 ppm (Rattus) 4 h
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation. Classification based on data available for ingredients.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Risk of serious damage to eyes.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)		
Cyclohexanone 108-94-1	EC50: =20mg/L (96h, Chlorella vulgaris)	LC50 96 h 481 - 578 mg/L (Pimephales promelas flow-through)	EC50 = 18.5 mg/L 5 min EC50 = 21.3 mg/L 10 min EC50 = 25 mg/L 5 min	EC50: =800mg/L (24h, Daphnia magna)		
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-09	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphnia Magna		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Methyl ethyl ketone 78-93-3	0.3	-
Cyclohexanone 108-94-1	0.86	-
Bisphenol-A-Epichlorhydrin Epoxy resin ≤ 700 MW 25068-38-6	3.26	31

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Methyl ethyl ketone 78-93-3	The substance is not PBT / vPvB
Cyclohexanone 108-94-1	The substance is not PBT / vPvB PBT assessment does not apply
Bisphenol-A-Epichlorhydrin Epoxy resin ≤ 700 MW 25068-38-6	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

Endocrine Disruptor Information

Chemical name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Bisphenol-A-Epichlorhydrin Epoxy resin ≤ 700 MW	Group III Chemical	-

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III, (D/E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None
Classification code	F1
Tunnel restriction code	(D/E)
Limited Quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	30

IMDG

14.1 UN number or ID number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III, (-9°C c.c.)
14.5 Marine pollutant	NP
14.6 Special Provisions	223, 955
Limited Quantity (LQ)	5 L
EmS-No	F-E, S-D
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A3
Limited Quantity (LQ)	10 L
ERG Code	3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No
Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 13-Oct-2021

SAFETY DATA SHEET

POLYPIPE GAP FILLER CEMENT CFC 100
Supersedes Date: 11-Sep-2020

Revision date 13-Oct-2021
Revision Number 1.05

Indication of changes

Revision note	Not applicable.
Training Advice	Provide adequate information, instruction, and training for operator
Further information	No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet