

# SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** POLYPIPE SILICONE SPRAY SG300  
**Container size:** 400ml  
**REACH registration notes:** All chemicals used in this product have been registered under REACH where required

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Universal lubricant.

### 1.3. Details of the supplier of the safety data sheet

**Supplier** Polypipe Building Products Ltd  
Broomhouse Lane  
Edlington  
Doncaster  
DN12 1ES  
Tel 01709770000  
Fax 01709770001

### 1.4. Emergency telephone number

**Emergency telephone** Polypipe Building Products Ltd. ++44 (0) 1709 770000 (Mon-Fri 09:00 - 17:00)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (EC 1272/2008)

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Skin Irrit. 2 - H315 STOT SE 3 -  
H336 **Environmental hazards** Aquatic Chronic 2 - H411

### 2.2. Label elements

#### Hazard pictograms



**Signal word** Danger

**Hazard statements** H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

|   |   |
|---|---|
| <b>Precautionary statements</b>               | <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Nosmoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>                   |
| <b>Contains</b>                               | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane   |
| <b>Supplementary precautionary statements</b> | <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P391 Collect spillage.</p> <p>P405 Store locked up.</p> |

## 2.3. Other hazards

Containers should be thoroughly emptied before disposal because of the risk of an explosion. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. In use may form flammable/explosive vapour-air mixture. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. This product does not contain any substances classified as PBT or vPvB. Vapours in high concentrations are narcotic.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

|  |                      |  |               |
|--|----------------------|--|---------------|
| <b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>  |                      |  | <b>30-60%</b> |
| CAS number: —  | EC number: 921-024-6 | REACH registration number: 01-2119475514-35-XXXX |               |
| <b>Classification</b><br>Flam. Liq. 2 - H225<br>Skin Irrit. 2 - H315<br>STOT SE 3 - H336<br>Asp. Tox. 1 - H304<br>Aquatic Chronic 2 - H411 |                      |  |               |
| <b>PETROLEUM GASES, LIQUEFIED, PETROLEUM GAS &lt;0.1% 1,3 BUTADIENE</b>  |                      |  | <b>30-60%</b> |
| CAS number: 68476-85-7   | EC number: 270-704-2 |  |               |
| <b>Classification</b><br>Press. Gas (Liq.) - H280  |                      |  |               |

The full text for all hazard statements is displayed in Section 16.

# SAFETY DATA SHEET

|                      |   |
|----------------------|---|
| Composition comments | CAS 68476-85-7 - Petroleum Gas, The substance contains less than 0.1% w/w 1,3-butadiene, meaning that the full harmonised classification regarding Muta. 1B H340 and Carc.1A H350 does not apply. |
|----------------------|---|

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

|                            |   |
|----------------------------|---|
| General information        | Move affected person to fresh air at once. Show this Safety Data Sheet to the medical personnel.  |
| Inhalation                 | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. If breathing stops, provide artificial respiration. Get medical attention immediately. |
| Ingestion                  | If throat irritation or coughing persists, proceed as follows. Rinse mouth thoroughly with water.   |
| Skin contact               | Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.  |
| Eye contact                | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes.   |
| Protection of first aiders | First aid personnel should wear appropriate protective equipment during any rescue.   |

### 4.2. Most important symptoms and effects, both acute and delayed

|                     |  |
|---------------------|--|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.   |
| Inhalation          | Coughing, chest tightness, feeling of chest pressure. Exposure may cause coughing or wheezing. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. |
| Ingestion           | There may be soreness and redness of the mouth and throat.   |
| Skin contact        | Prolonged contact may cause redness, irritation and dry skin.  |
| Eye contact         | There may be irritation and redness. Eyes may water profusely.   |

### 4.3. Indication of any immediate medical attention and special treatment needed

|                      |  |
|----------------------|--|
| Notes for the doctor | Show this safety data sheet to the doctor in attendance. The following symptoms may occur: Nausea, headache, dizziness, coughing and breathing difficulty. |
| Specific treatments  | Treat symptomatically.   |

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

|                                |  |
|--------------------------------|--|
| Suitable extinguishing media   | Water spray, dry powder or carbon dioxide. Alcohol-resistant foam.     |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |

### 5.2. Special hazards arising from the substance or mixture

|                  |   |
|------------------|---|
| Specific hazards | Containers can burst violently or explode when heated, due to excessive pressure build-up. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Bursting aerosol containers may be propelled from a fire at high speed. |
|------------------|---|

# SAFETY DATA SHEET

**Hazardous combustion products**

Oxides of carbon. Acid smoke or fumes.

**5.3. Advice for firefighters****Protective actions during firefighting**

Use water to keep fire exposed containers cool and disperse vapours. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters**

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures****Personal precautions**

Wear protective clothing as described in Section 8 of this safety data sheet. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Do not breathe vapour. Avoid contact with eyes and prolonged skincontact.

**For non-emergency personnel** For the greatest protection, clothing should include anti-static overalls, boots and gloves.

**For emergency responders** For the greatest protection, clothing should include anti-static overalls, boots and gloves.

**6.2. Environmental precautions****Environmental precautions**

Contain the spillage using bunding. Contain spillage with sand, earth or other suitable non-combustible material.

**6.3. Methods and material for containment and cleaning up****Methods for cleaning up**

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoidwater contacting spilled material or leaking containers. Approach the spillage from upwind.  
Take precautionary measures against static discharge. Use only non-sparking tools.

**6.4. Reference to other sections****Reference to other sections**

For personal protection, see Section 8. See Section 7 for information on safe handling. Forwaste disposal, see Section 13.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling****Usage precautions**

Keep away from heat, sparks and open flame. Static electricity and formation of sparks mustbe prevented. Wear protective clothing as described in Section 8 of this safety data sheet. Read and follow manufacturer's recommendations. Do not use in confined spaces without adequate ventilation and/or respirator. Do not eat, drink or smoke when using this product.

**Advice on general occupational hygiene**

Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas. Wash after use and before eating, smoking and using the toilet. Do not smoke in work area. Clean equipment and the work areaevery day.

**7.2. Conditions for safe storage, including any incompatibilities**

# SAFETY DATA SHEET

**Storage precautions** Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Store in tightly closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents. Store away from the following materials: Alkalis.

**Storage class** Extremely Flammable Aerosol

## 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

**Usage description** Store in a flammable storage cupboard according to national regulations. Solvent based aerosol.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750  
mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 1250 ppm 2180  
mg/m<sup>3</sup> WEL = Workplace Exposure Limit.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### DNEL

Consumer - Oral; Long term systemic effects: 699 mg/kg/day  
Workers - Oral; Long term systemic effects: 2035 mg/kg/day  
Consumer - Dermal; Long term systemic effects: 699  
mg/kg/day Workers - Dermal; Long term systemic effects: 773  
mg/kg/day Consumer - Inhalation; Long term systemic effects:  
608 mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure. Refer to protective measures listed in sections 7 and 8.

#### Personal protection

Wear protective work clothing.

#### Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

#### Hand protection

(PE/PA/PE), 2.5mil (0.06mm), >480 min. To protect hands from chemicals, gloves should comply with European Standard EN374. Nitrile rubber. Polyvinyl chloride (PVC). For users with sensitive skin, it is recommended that suitable protective gloves are worn. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

#### Other skin and body protection

Provide eyewash station. Avoid contact with skin. Wear suitable coveralls to prevent exposure to the skin.

# SAFETY DATA SHEET

|  |   |
|--|---|
| <b>Hygiene measures</b>                | Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Use appropriate hand lotion to prevent defatting and cracking of skin. Wash at the end of each work shift and before eating, smoking and using the toilet.   |
| <b>Respiratory protection</b>          | If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. For short term use an AX filter is recommended. |
| <b>Thermal hazards</b>                 | Extremely cold, can cause frost bite.   |
| <b>Environmental exposure controls</b> | Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.  |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |  |
|---|--|
| <b>Appearance</b>                                   | Aerosol.   |
| <b>Colour</b>                                       | Clear.   |
| <b>Odour</b>  | Hydrocarbons.  |
| <b>Odour threshold</b>                              | Data lacking.  |
| <b>pH</b>   | pH (concentrated solution): 7  |
| <b>Melting point</b>                                | Data lacking.  |
| <b>Initial boiling point and range</b>              | 60°C @ 760 mm Hg. Boiling point of hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics. |
| <b>Flash point</b>                                  | No information available.  |
| <b>Evaporation rate</b>                             | Not available.   |
| <b>Evaporation factor</b>                           | Not available.   |
| <b>Flammability (solid, gas)</b>                    | No specific test data are available.   |
| <b>Upper/lower flammability or explosive limits</b> | Not available.   |
| <b>Other flammability</b>                           | No specific test data are available.   |
| <b>Vapour pressure</b>                              | 5.5 bar @ 20°C 9.5 bar @ 50°C  |
| <b>Vapour density</b>                               | Not available.   |
| <b>Relative density</b>                             | Not available.   |
| <b>Bulk density</b>                                 | Not applicable.  |
| <b>Solubility(ies)</b>                              | Insoluble in water.  |
| <b>Partition coefficient</b>                        | Not available.   |
| <b>Auto-ignition temperature</b>                    | Not available.   |
| <b>Decomposition Temperature</b>                    | Not available.   |
| <b>Viscosity</b>                                    | Not available.   |
| <b>Explosive properties</b>                         | In use may form flammable/explosive vapour-air mixture.                                |
| <b>Explosive under the influence of a flame</b>     | Yes  |

# SAFETY DATA SHEET

|                             |   |
|-----------------------------|---|
| <b>Oxidising properties</b> | Does not meet the criteria for classification as oxidising.   |
| <b>Comments</b>             | A flash point method is not available but the major hazardous component, the Propellant has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower. |

## 9.2. Other information

|                                  |   |
|----------------------------------|---|
| <b>Other information</b>         | Not available.  |
| <b>Volatile organic compound</b> | This product contains a maximum VOC content of 536 g/l. |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

|                   |   |
|-------------------|---|
| <b>Reactivity</b> | Stable under recommended transport or storage conditions. |
|-------------------|---|

### 10.2. Chemical stability

|                  |  |
|------------------|--|
| <b>Stability</b> | Stable at normal ambient temperatures and when used as recommended. Highly volatile. |
|------------------|--|

### 10.3. Possibility of hazardous reactions

|   |  |
|---|--|
| <b>Possibility of hazardous reactions</b> | Will not polymerise. In use may form flammable/explosive vapour-air mixture. |
|---|--|

### 10.4. Conditions to avoid

|                            |  |
|----------------------------|--|
| <b>Conditions to avoid</b> | Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Avoid the accumulation of vapours in low or confined areas. |
|----------------------------|--|

### 10.5. Incompatible materials

|                           |  |
|---------------------------|--|
| <b>Materials to avoid</b> | Strong acids. Strong oxidising agents. Strong alkalis. |
|---------------------------|--|

### 10.6. Hazardous decomposition products

|   |                   |
|---|-------------------|
| <b>Hazardous decomposition products</b> | Oxides of carbon. |
|---|-------------------|

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|   |   |
|---|---|
| <b>General information</b>              | Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.  |
| <b>Inhalation</b>                       | High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation. There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. |
| <b>Ingestion</b>                        | May cause nausea, headache, dizziness and intoxication.   |
| <b>Skin contact</b>                     | Prolonged contact may cause redness, irritation and dry skin.   |
| <b>Eye contact</b>                      | There may be irritation and redness. Eyes may water profusely.  |
| <b>Acute and chronic health hazards</b> | Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Frequent inhalation of vapours may cause respiratory allergy.  |

# SAFETY DATA SHEET

**Route of exposure** Inhalation Skin absorption

**Medical symptoms** Narcotic effect. Vapours may cause drowsiness and dizziness

## Toxicological information on ingredients.

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rat

#### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 2,000.0

**Species** Rabbit

#### Skin corrosion/irritation

**Skin corrosion/irritation** Skin irritation.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

#### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

#### Aspiration hazard

**Aspiration hazard** May be fatal if swallowed and enters airways.



# SAFETY DATA SHEET

**PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE**

**Toxicological effects** Information given is based on data of the components and of similar products

**Acute toxicity - oral**

**Notes (oral LD<sub>50</sub>)** Not applicable.

**Acute toxicity - dermal**

**Notes (dermal LD<sub>50</sub>)** Not applicable.

**Acute toxicity - inhalation**

**Notes (inhalation LC<sub>50</sub>)** LC<sub>50</sub> >20 mg/l, Inhalation, Rat

**Skin corrosion/irritation**

**Skin corrosion/irritation** Not irritating.

**Serious eye damage/irritation**

**Serious eye damage/irritation** Not irritating.

**Respiratory sensitisation**

**Respiratory sensitisation** Not sensitising.

**Skin sensitisation**

**Skin sensitisation** Not sensitising.

**Germ cell mutagenicity**

**Genotoxicity - in vitro** This substance has no evidence of mutagenic properties. **Carcinogenicity**

**Carcinogenicity** Carcinogenicity in humans is not expected.

**Reproductive toxicity**

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Does not contain any substances known to be toxic to reproduction.

# SAFETY DATA SHEET

## Specific target organ toxicity - single exposure

**STOT - single exposure** A single exposure may cause the following adverse effects: Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.

## Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

## Aspiration hazard

**Aspiration hazard** Not anticipated to present an aspiration hazard, based on chemical structure.

**Inhalation** May cause respiratory system irritation.

**Skin contact** Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

**Route of exposure** Inhalation Skin and/or eye contact

## SECTION 12: Ecological information

**Ecotoxicity** The product contains substances which are toxic to aquatic organisms, and which may cause long-term adverse effects in the aquatic environment.

### Ecological information on ingredients.

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Ecotoxicity** Information given is based on data of the components and of similar products.

### 12.1. Toxicity

**Toxicity** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

### Ecological information on ingredients.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, : 1-10 mg/l, Fish  
NOEC, : 1-10 mg/l, Fish

**Acute toxicity - aquatic plants** LC<sub>50</sub>, : 10-100 mg/l, Algae

**Acute toxicity - microorganisms** LC<sub>50</sub>, : 1-10 mg/l, Activated sludge  
NOEC, : 0.1-1 mg/l, Activated sludge

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Toxicity** Not regarded as dangerous for the environment. The product is not believed to present a hazard due to its physical nature. Highly volatile.

### 12.2. Persistence and degradability

### Ecological information on ingredients.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Persistence and degradability** No data available.

# SAFETY DATA SHEET

## PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

### Persistence and degradability

The product is readily biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

### Ecological information on ingredients.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Bioaccumulative potential Not available.

## PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Bioaccumulative potential Bioaccumulation is unlikely.

### 12.4. Mobility in soil

Mobility Readily absorbed into soil.

### Ecological information on ingredients.

## PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

### Mobility

The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

### Ecological information on ingredients.

## PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

Other adverse effects Not available.

### Ecological information on ingredients.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

### Other adverse effects

The product contains a substance which is toxic to aquatic organisms, and which may cause long-term adverse effects in the aquatic environment.

# SAFETY DATA SHEET

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

## Ecological information on ingredients.

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

## 12.6. Other adverse effects

**Other adverse effects** Not available.

## Ecological information on ingredients.

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Other adverse effects** The product contains a substance which is toxic to aquatic organisms, and which may cause long-term adverse effects in the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Ensure containers are empty before discarding (explosion risk). Must not be disposed of together with household waste.

**Disposal methods** Do not puncture or incinerate, even when empty. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

**Waste class** Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous residues), Empty Aerosol: 15 01 04 (No hazardous residues).

## SECTION 14: Transport information

### 14.1. UN number

**UN No. (ADR/RID)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

**UN No. (ADN)** 1950

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** AEROSOLS

**Proper shipping name (IMDG)** AEROSOLS

**Proper shipping name (ICAO)** AEROSOLS

**Proper shipping name (ADN)** AEROSOLS

### 14.3. Transport hazard class(es)

**ADR/RID class** 2.1

**ADR/RID classification code** 5F

**ADR/RID label** 2.1

# SAFETY DATA SHEET

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



## 14.4. Packing group

Not applicable.

## 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



## 14.6. Special precautions for user

IMDG Code segregation group SG69

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

|   |   |
|---|---|
| National regulations                            | The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).<br>Control of Substances Hazardous to Health Regulations 2002 (as amended).<br>Health and Safety at Work etc. Act 1974 (as amended).  |
| EU legislation                                  | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). |
| Guidance  | Workplace Exposure Limits EH40.   |
| Authorisations (Annex XIV Regulation 1907/2006) | No specific authorisations are known for this product.  |
| Restrictions (Annex XVII Regulation 1907/2006)  | No specific restrictions on use are known for this product.   |

# SAFETY DATA SHEET

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

**Classification procedures according to Regulation (EC) 1272/2008**  
Aerosol 1 - H222, H229: Weight of evidence. Skin Irrit. 2 - H315: Calculation method.  
AquaticChronic 2 - H411: Calculation method. STOT SE 3 - H336: Calculation method.

**Issued by** Technical Department

**Revision date** 11/06/2020

**Revision** 5.1

**Supersedes date** 28/01/2016

**Hazard statements in full**  
H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H229 Pressurised container: may burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

## Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated.

However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

**End of Safety Data Sheet**