## **PRODUCT INFORMATION**

P1

**ISSUE 4 - APRIL 2018** 

Ridgisewer is a range of structured wall gravity sewer pipes and fittings available in diameters from 400-900mm. The complete system includes a range of couplings, seals, bends, junctions, specialist fabrications and saddles.

The system\* is manufactured in accordance to BS EN 13476-1 and WIS 4-35-01 v2 and has adequate resistance to the type and quantities of chemicals likely to be found in domestic sewerage.



## **Applications**

Ridgisewer provides robust, chemical and sewer gas resistant sewer pipes for new and replacement gravity sewer systems.

## **Key benefits**

- Fully compliant with BS EN 13476-1 & WIS 4-35-01 v2\*
- BSI Kitemarked & BBA Approved\*
- Adoptable by water companies\*
- 400-600mm diameters manufactured to stiffness classification 8
   terracotta polypropylene pipes with blue inners
- 750-900mm diameters manufactured to stiffness classification 4
   black polyethylene pipes with blue inners and a terracota band
- · Lighter in weight for increased Health and Safety benefits
- Structured wall pipe for high ring stiffness and strength
- Integral sockets for quicker installation and greater leak tightness
- Strong, flexible pipe wall withstands ground movement and differential settlement
- Chemical, impact and abrasion resistant
- · Resistant to sulphate attack and corrosion by sewer gas
- Saddle connectors are available\*
- Meets WRc Code of Practice for high pressure water jetting tolerance\*

RIDGISEWER INTEGRALLY SOCKETED PIPE					
NOMINAL SIZE ID (mm)	OD (mm)	CODE	LENGTH (m)	WEIGHT kg/m	PACK QTY
400	458	RSW400X3IS8	3	9	5
450	513	RSW450X3IS8	3	13	4
500	570	RSW500X3IS8	3	14	4
600	672	RSW600X3IS8	3	19	2
750	852	RSW750X3IS4/1	3	30	2
900	1022	RSW900X3IS4/1	3	39	2

6m lengths available on request, subject to minimum order quantity. Sizes 1050-3000mm are available as Ridgistorm-XL.

JOINTING					
COUPLING CODE	SEAL CODE				
RSWC4008	SRSW4008				
RSWC4508	SRSW4508				
RSWC5008	SRSW5008				
RSWC6008	SRSW6008				
RSWC750DS/1	SRSW750/1				
RSWC900DS/1	SRSW900/1				
	RSWC4008 RSWC4508 RSWC5008 RSWC6008 RSWC750DS/1				





\*For sizes up to and including 600mm diameter.

750mm and 900mm diameter have approval pending for WIS, BBA and adoption by water companies.

All descriptions and illustrations in this publication are intended for guidance only and shall not constitute a 'sale by description'. All dimensions given are nominal and Polypipe may modify and change the information, products and specifications from time to time for a variety of reasons, without prior notice. The information in this publication is provided 'as is' on April 2018. Updates will not be issued automatically. This information is not intended to have any legal effect, whether by way of advice, representation or warranty (express or implied). We accept no liability whatsoever (to the extent permitted by law) if you place any reliance on this publication you must do so at your own risk. All rights reserved. Copyright in this publication belongs to Polypipe and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person without prior consent. Polypipe is a registered trademark of Polypipe. All Polypipe products are protected by Design Right under CDPA 1988. Copyright © 2018 Polypipe. All rights reserved.

