

lability in connection therewith. Further information with regard to liabilities may be found at www.polypipe.com/disclaimer.

DARD DETAILS

16/03/16 RST_SD_EG_001 స్ట FOR INFORMATION AS SHOWN

RIDGISTORM-XL NOTES

chambers. All pipes and fittings may be manufactured with consist of pipework, fittings, access and component the appropriate strength and stiffness to meet project specific requirements. infiltration systems. Factory fabricated modular solutions can engineer complete storage tanks for attenuation and robust modular underground storage tanks. Polypipe Civils Ridgistorm-XL is an ideal solution to form unique and

- All dimensions in millimetres, unless otherwise stated. All dimensions are nominal and may vary within
- manufacturing or construction tolerances.
- All site temporary and enabling works by others.
- Ridgistorm-XL units to be installed in accordance with consideration to the requirements of the organisation technical guidance for further information); giving due who will be taking ultimate ownership of the Polypipe Civils recommendations (refer to Polypipe nstallation
- SN2 pipe; corresponding to the standardised pipe Dimensions are based on a minimum stiffness class profiles current at the time of this drawing's issue.
- engineers before final design or construction activities document should be sought from the consulting Confirmation of the information contained within this This drawing is intended for guidance only.
- to site without direct means of lifting incorporated. The circumstances of the lift, and provide slings and/or lift supervisor must assess and plan the lift, in the Unless otherwise stated, all Ridgistorm-XL is supplied other controls as deemed necessary to ensure a safe
- trafficking and proposed Ridgistorm-XL pipe Minimum and maximum cover depths applicable, dictated by the expected native ground conditions