

ELECTROFUSION JOINT / EXTRUSION WELDED JOINT

IDEALISED NOMINAL JOINT DIMENSIONS

Ridgistorm RST Ø750mm Pipe size 07 PRODUCT CODE EXPLANATION SN1 and above available Pipe stiffness class SN2. Stiffness classes 20 *min 1.25m Length 6m 60 Extrusion welded Electro-fusion/ Ш

IOINT TYPES AVAILABLE

(Based on pipe diameter)

For furthe to the Rid	3000	2700	2400	2100	1800	1500	1200	1050	900	750	Pipe I.D.	
Fige suilitiess class on a did below only. For further guidance on jointing please refer to the Ridgistorm-XL Technical Manual.	* *	*	√ *	V	Electro- fusion							
on jointing p	ond h	*	×	×	V	V	V	√	1	V	Ring Seal	
lease refer fanual	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	<	~	· · ·	<	<	· ·	~	· /	×	Extrusion weld	

Ridgistorm

Pipe size Ø750mm

SN1 and above available

*min 1.25m Length 6m

Ring Seal Joint

Stiffness classes

Pipe stiffness class SN2.

RST

07

20

60

S

PRODUCT CODE EXPLANATION

Polypipe

Polypipe Civils

Charnwood Business Park, North Road, Loughborough, Leicestershire. LE11 1LE Tel: 01509 615100 Fax: 01509 615215 www.polypipe.com/civils www.polypipe.com/wms

iability in connection therewith. Further information with regard to liabilities may be found at www.polypipe.com/disclaimer.

suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user and the user must assume all risk and requirements of our products for a proposed application and expected site conditions; expert advice should be sought in this respect. Final determination of the contract or intended contract with the user. The information within this document should not be solely relied upon to determine the suitability or installation The information in this document is of an illustrative nature and is supplied by Polypipe Civils without charge. This document does not form the whole or any part of a

TYPICAL SOCKET AND SP

RST_SD_FT_002

స్ట

AS SHOWN

FOR INFORMATION

RIDGISTORM-XL STAN DARD DETAILS

GOT JOINT DETAILS 16/03/16

NOTES

All dimensions in millimetres, unless otherwise stated.

All dimensions are nominal and may vary within

- manufacturing or construction tolerances.
- ₽ω All site temporary and enabling works by others.
- Ridgistorm-XL units to be installed in accordance with consideration to the requirements of the organisation technical guidance for further information); giving due who will be taking ultimate ownership of the Polypipe Civils recommendations (refer to Polypipe

DEALISED NOMINAL JOINT DIMENSI

SNS

nstallation

RING SEAL JOINT

- S SN2 pipe; corresponding to the standardised pipe Dimensions are based on a minimum stiffness class profiles current at the time of this drawing's issue.
- <u>ი</u> engineers before final design or construction activities Confirmation of the information contained within this document should be sought from the consulting This drawing is intended for guidance only.
- 7. to site without direct means of lifting incorporated. The Unless otherwise stated, all Ridgistorm-XL is supplied other controls as deemed necessary to ensure a safe lift supervisor must assess and plan the lift, in the circumstances of the lift, and provide slings and/or
- œ trafficking and proposed Ridgistorm-XL pipe Minimum and maximum cover depths applicable, dictated by the expected native ground conditions,